


USB to 8-Port RS-232 DB9 Serial Interface Adapter




DB9M Connector



RS232 Pin Out

Pin #	Signal
1	DCD
2	RX
3	TX
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

DB9M RS-232 Loopback





Part: 2801 Model: SeaLINK+8/232

Description

The SeaLINK® 2801 USB serial I/O adapter provides eight RS-232 serial ports for USB connectivity to legacy or non-USB compliant devices.

The 2801 is housed in a rugged metal enclosure making it ideal for rugged and industrial environments. The adapter integrates Sealevel's SeaLATCH locking USB port, which is fully compatible with standard USB cables. When used with the included USB cable with a locking type B connector, the metal thumbscrew provides a secure connection to the device and prevents accidental cable disconnection. Additionally, the high-retention type B connector helps prevent unintentional separation from a standard USB cable.

Sealevel SeaCOM USB software drivers and utilities make installation and operation easy using Microsoft Windows and Linux operating systems. After installing the software, simply plug the 2801 into an available USB port. The serial ports are recognized as standard COM ports by the host system enabling compatibility with legacy software.

All Sealevel SeaLINK USB serial adapters use a state-machine architecture that greatly reduces the host computer's overhead when communicating over multiple serial ports simultaneously while supporting data rates to 460.8K bps. Status LEDs on the front of the enclosure indicate power and serial data activity on each port.

Standard operating temperature range is 0°C to 70°C and extended temperature range (-40°C to 85°C) is optional.

Do you know that adapter design can impact your application? Find out how in this [USB Serial Performance](#)

report. Category: [Eight](#)

[Port](#)

Additional information

Family	SeaLINK
Max Data Rate	460.8K bps
Dimensions	8.7" (L) x 6.1" (W) x 2.0" (H)
Electrical Interface	RS-232
High Retention USB	Yes
Humidity Range	10 – 90% Relative Humidity, Non-Condensing
Host Interface(s)	USB
Max Data Distance	50 feet
Communications Chip	USB/UART
# of Ports	8
Operating Temperature	0°C to 70°C (32°F to 158°F)
Power Requirement	+5V @ 500mA
RoHS Compliant	Yes
SeaLATCH Locking USB	Yes

Serial Connector(s)	DB9M
Storage Temperature	-50°C to 105°C (-58°F to 221°F)
USB Powered	Yes
USB Specification	1.1 Compliant 2.0 Compatible

Compliant with RoHS and WEEE directives

High-speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO

Data rates to 460.8K bps

All modem control signals implemented

Serial and USB activity LEDs

Hot-swappable

Powered by USB connection

Sealevel's SeaLATCH locking USB port provides secure connection with SeaLATCH

USB cables via metal thumbscrews

Sealevel software supports Windows and Linux operating systems

DB-9M connectors

Includes 6' USB type A to SeaLATCH USB type B device cable (Item#

CA356)